



THE LUXURY TRAVELLING LOO COMPANY

MODUVAC® Mains Loo System Disabled Modules

The Disabled Modules are units that are positioned ideally outside or even inside a structure. They come with ramps for access or the client may build their own flooring to reach the level of the floor.

- Porcelain hand basin with hot and cold lever taps
- Contrasting colour hand rails
- Emergency lighting and alarm
- Hand towel, loo paper and soap dispensers
- Fully compliant with Doc M building regulations

The units are connected to a fresh water flush system emptying either into a waste tank provided by IGLOOS or linked to a mains drain via a 4" mains connection. There is no requirement for chemical. If the units are operating on a system requiring waste tanks, these should be situated outside a structure.

Requirements for operation

- Equipment is delivered on an articulated lorry so access should be ensured for the vehicle and forklift access into position.
- Constant power supply of a 16amp C form is required for installation and during the event.
- Constant fresh water supply with good pressure for installation and during the event. The fresh water is necessary for both the hand basins and loo pan.

Accessories

- Consumables – Scottish Fine Soaps and Hand Lotion, loo paper and paper hand towels are supplied as standard.

MODUVAC® Layouts DISABLED MODULE

1 WC, 1 hand basin

Measures:
7'6" (2.34 m) length
5'2" (1.55 m) width
7'5" (2.30 m) high



...beautiful loos ...beautiful events